

Command GetClientDetails - Step 1

Request url: `your_api_url/getclientdetails?clientId={clientid}`

Response will return in XML format

Command Response:

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <result>0</result>
  <comment>OK</comment>
  <addinfo>Name Surname | |Current balance</addinfo>
</response>
```

Example:

1) Request: `your_api_url/getclientdetails?clientId=1234567890`

Response:

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <result>0</result>
  <comment>OK</comment>
  <addinfo>Jeyhun Gasimzade | |2.00</addinfo>
</response>
```

2) Request: `your_api_url/getclientdetails?clientId=1234567890`

Response:

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <result>1</result>
  <comment>NOT OK</comment>
  <addinfo></addinfo>
</response>
```

Description of tags

Tags name	Description
response	Body
result	Result of the response. Only two variants possible. 0 – client is valid. Payment allowed. 1 – client is not valid or not found in DB
comment	Optional tag that returns description of the result.
addinfo	Will return information about client. Many information can be used in this tag. In order to separate values symbols have to be used.

Command Pay - Step 2

Request url:

`your_api_url/pay?clientId={clientid}&sum={sum}&txn_id={txn_id}&terminal={terminal}`

Response will return in XML format

Command Response:

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <txn_id>SomePrefix0123456789</txn_id >
  <sum>1.00</sum>
  <result>0</result>
  <comment>OK</comment>
</response>
```

Example:

- 1) Request: `your_api_url/pay?clientId=1234567890&sum=1.00&txn_id=SomePrefix0123456789&terminal=GoldenPay`

Response:

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <txn_id>SomePrefix0123456789</txn_id >
  <sum>1.00</sum>
  <result>0</result>
  <comment>OK</comment>
```

```
</response>
```

2) Request:

```
your_api_url/pay?clientId=1234567890&sum=1.00&txn_id=GoldenPay12345&terminal=GoldenPay
```

Response:

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <txn_id>SomePrefix0123456789</txn_id >
  <sum>1.00</sum>
  <result>1</result>
  <comment>NOT OK</comment>
</response>
```

Description of tags

Tag name	Description
response	Body
txn_id	Returns txn_id
sum	Amount of payment
result	Result of the response. Only two variants possible. 0 – Payment accepted. 1 – something went wrong
comment	Optional tag that returns description of the result.

Command STATUS - Step 3

Request url: `your_api_url/status?txn_id={txn_id}`

Response will return in XML format

Command Response:

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <result>0</result>
```

```
<txn_id>SomePrefix0123456789</txn_id>
<comment>OK</comment>
</response>
```

Example:

1) Request: your_api_url/status?txn_id= SomePrefix0123456789

Response:

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <result>0</result>
  <txn_id>SomePrefix0123456789</txn_id>
  <comment>OK</comment>
</response>
```

2) Request: your_api_url/status?txn_id= SomePrefix0123456789

Response:

```
<?xml version="1.0" encoding="UTF-8"?>
<response>
  <result>1</result>
  <txn_id>SomePrefix0123456789</txn_id>
  <comment>NOT OK</comment>
</response>
```

Description of tags

Tags name	Description
response	Body
txn_id	Returns txn_id
result	Result of the response. Only two variants possible. 0 – client is valid. Payment allowed. 1 – client is not valid or not found in DB
comment	Optional tag that returns description of the result.