

Dv

- TP_ID (internet_main.tp_id tarif_plans.tp_id), **Dv (dv_main.tp_id tarif_plans.id)**
-
- Dhchosts Internet (-)
- Dhchosts
- isc dhcp billd isc_dhcp

config.pl

: Dv, Dhchosts, Ipn, Vlan

```
@MODULES = (  
  'Internet'  
);
```

internet_log_intervals, internet_main, internet_online, internet_log, internet_users_pool, /usr/abills/db/abills.sql

, Dv/DHCP/IPN

```

INSERT INTO internet_main (
  uid,
  tp_id,
  logins,
  registration,
  ip,
  filter_id,
  speed,
  netmask,
  cid,
  password,
  disable,
  join_service,
  turbo_mode,
  free_turbo_mode,
  activate,
  expire,
  login,
  personal_tp,
  detail_stats,
  nas_id,
  port,
  vlan,
  server_vlan,
  cpe_mac,
  ipn_activate
)

SELECT dv.uid,
  if(tp.tp_id IS NULL, 0, tp.tp_id),
  dv.logins,
  dv.registration,
  if(dh.ip IS NULL, dv.ip, dh.ip),
  dv.filter_id,
  dv.speed,
  dv.netmask,
  if (dh.mac <> '00:00:00:00:00:00', dh.mac, dv.cid),
  dv.password,
  dv.disable,
  dv.join_service,
  dv.turbo_mode,
  dv.free_turbo_mode,
  '0000-00-00',
  dv.expire,
  dv.dv_login,
  dv.personal_tp,
  dv.traf_detail,
  if (dh.nas IS NULL, 0, dh.nas),
  if (dh.ports<>' ', dh.ports, dv.port),
  if (dh.vid IS NULL, 0, dh.vid),
  if (dh.server_vid IS NULL, 0, dh.server_vid),
  '',
  if (dh.server_vid IS NULL, 0, dh.ipn_activate)
FROM dv_main dv
  LEFT JOIN tarif_plans tp ON (dv.tp_id=tp.id AND tp.module='Dv')
  LEFT JOIN dhcphosts_hosts dh ON (dv.uid=dh.uid);

UPDATE internet_main im, users u SET im.activate=u.activate WHERE im.uid=u.uid;

```

```

UPDATE shedule SET module='Internet' WHERE module='Dv';

```

()

```

INSERT INTO internet_log (
  start,
  tp_id,
  duration,
  sent,
  recv,
  sum,
  port_id,
  nas_id,
  ip,
  acct_session_id,
  cid,
  bill_id,
  uid,
  terminate_cause,
  acct_input_gigawords,
  acct_output_gigawords
)
SELECT
  dv.start,
  if(tp.tp_id IS NULL, 0, tp.tp_id),
  dv.duration,
  dv.sent,
  dv.recv,
  dv.sum,
  dv.port_id,
  dv.nas_id,
  dv.ip,
  dv.acct_session_id,
  dv.CID,
  dv.bill_id,
  dv.uid,
  dv.terminate_cause,
  dv.acct_input_gigawords,
  dv.acct_output_gigawords
FROM `dv_log` dv
LEFT JOIN `tarif_plans` tp ON (tp.id=dv.tp_id);

```

```

INSERT INTO internet_log_intervals SELECT * FROM dv_log_intervals;

```

Internet+
config.pl

```

$AUTH{accel_ppp}='Auth2';
$ACCT{accel_ppp}='Acct2';
....
$AUTH{mpd5}='Auth2';

```